

Tipo di avviatore	Modello	Codice	Impugnatura Tipo	Campo di coppia su giunzione elastica		Velocità a vuoto giri/1'	Avviamento Tipo	Reversibilità Tipo	Peso kg	Dimensioni (mm) Øxh	Consumo aria l/s	Accessori Attacco	Livello di pressione sonora dBA	Vibrazioni m/s²
				min.	max.									
	15C2A	112514372		0,4 ÷ 2,0		2000			0,58	38x230	4,0	⬡ F 1/4"	73	< 2,5
	15C3A	112514373		0,4 ÷ 3,5		1400			0,59	38x230	5,5	⬡ F 1/4"	73	< 2,5
	15C4A	112514374		0,4 ÷ 4,5		950			0,59	38x230	5,5	⬡ F 1/4"	73	< 2,5
	15C5A	112514375		0,4 ÷ 5,0		650			0,59	38x230	5,5	⬡ F 1/4"	73	< 2,5
	15C5A250	112509851		0,4 ÷ 5,0		250			0,65	38x240	5,5	⬡ F 1/4"	73	< 2,5
	15C5A150	112509935		0,4 ÷ 5,0		150			0,65	38x240	5,5	⬡ F 1/4"	73	< 2,5
	15C2AL	112514382		0,4 ÷ 2,0		2000			0,59	38x228	4,0	⬡ F 1/4"	73	< 2,5
	15C3AL	112514383		0,4 ÷ 3,5		1400			0,60	38x228	5,5	⬡ F 1/4"	73	< 2,5
	15C4AL	112514384		0,4 ÷ 4,5		950			0,60	38x228	5,5	⬡ F 1/4"	73	< 2,5
	15C5AL	112514385		0,4 ÷ 5,0		650			0,60	38x228	5,5	⬡ F 1/4"	73	< 2,5
	15C5AL250	112509921		0,4 ÷ 5,0		250			0,66	38x242	5,5	⬡ F 1/4"	73	< 2,5
	15C5AL150	112509925		0,4 ÷ 5,0		150			0,66	38x242	5,5	⬡ F 1/4"	73	< 2,5
	15C2APA	112514522		0,6 ÷ 2,2		2200			0,70	31x178x156	6	⬡ F 1/4"	71	< 2,5
	15C4APA	112514523		0,4 ÷ 3,5		1400			0,72	31x178x156	6	⬡ F 1/4"	71	< 2,5
	15C4APA	112514524		0,4 ÷ 4,5		950			0,72	31x178x156	6	⬡ F 1/4"	71	< 2,5
	15C5APA	112514525		0,4 ÷ 5,0		650			0,72	31x178x156	6	⬡ F 1/4"	71	< 2,5
	15C2AP	112514532		0,6 ÷ 2,2		2200			0,70	37x209x157	6	⬡ F 1/4"	71	< 2,5
	15C3AP	112514533		0,4 ÷ 3,5		1400			0,72	37x209x157	6	⬡ F 1/4"	71	< 2,5
	15C5AP	112514534		0,4 ÷ 4,5		950			0,72	37x209x157	6	⬡ F 1/4"	71	< 2,5
	15C5AP	112514535		0,4 ÷ 5,0		650			0,72	37x209x157	6	⬡ F 1/4"	71	< 2,5
	15C5AP250	112307250		0,4 ÷ 5,0		250			0,78	37x221x157	6	⬡ F 1/4"	73	< 2,5
	15C5AP150	112507063		0,4 ÷ 5,0		150			0,78	37x221x157	6	⬡ F 1/4"	73	< 2,5
	15C2A90	112593942		0,8 ÷ 2		2000			0,70	vedi pag. 10	4,0	⬡ M 1/4"	73	< 2,5
	15C3A90	112593943		0,8 ÷ 3		1400			0,70	vedi pag. 10	5,5	⬡ M 1/4"	73	< 2,5
	15C4A90	112593944		0,8 ÷ 4		950			0,70	vedi pag. 10	5,5	⬡ M 1/4"	73	< 2,5
	15C5A90	112593945		0,8 ÷ 5		650			0,70	vedi pag. 10	5,5	⬡ M 1/4"	73	< 2,5
	15C2A30	112533942		0,8 ÷ 2		2000			0,70	vedi pag. 10	4,0	⬡ M 1/4"	73	< 2,5
	15C3A30	112533943		0,8 ÷ 3		1400			0,70	vedi pag. 10	5,5	⬡ M 1/4"	73	< 2,5
	15C4A30	112533944		0,8 ÷ 4		950			0,70	vedi pag. 10	5,5	⬡ M 1/4"	73	< 2,5
	15C5A30	112533945		0,8 ÷ 5		650			0,70	vedi pag. 10	5,5	⬡ M 1/4"	73	< 2,5
	15C5A90-250	112507027		0,8 ÷ 5		250			0,76	vedi pag. 10	5,5	⬡ M 1/4"	73	< 2,5
	15C5A90-150	112509924		0,8 ÷ 5		150			0,90	vedi pag. 10	5,5	⬡ M 1/4"	73	< 2,5

Modelli con reversibilità sul pulsante

15C2APA-2200-R	112514551		0,6 ÷ 2,2		2200			0,75	37x186x155	6	⬡ F 1/4"	71	< 2,5
15C3APA-1400-R	112514552		0,4 ÷ 3,5		1400			0,77	37x186x155	6	⬡ F 1/4"	71	< 2,5
15C4APA-950-R	112514553		0,4 ÷ 4,5		950			0,77	37x186x155	6	⬡ F 1/4"	71	< 2,5
15C5APA-650-R	112514554		0,4 ÷ 5		650			0,77	37x186x155	6	⬡ F 1/4"	71	< 2,5
15C5APA-250-R	112507064		0,4 ÷ 5		250			0,82	37x198x155	6	⬡ F 1/4"	71	< 2,5
15C5APA-150-R	112507065		0,4 ÷ 5		150			0,82	37x198x155	6	⬡ F 1/4"	71	< 2,5