


Valvole a scarico rapido

■ HC06

Valvola a scarico rapido



HC0600M5	M5
HC060018	G1/8
HC060014	G1/4
HC060038	G3/8
HC060012	G1/2
HC060034	G3/4
HC060001	G1

attacco	Portata a 6 bar (NI/min)	
	1 → 2	2 → 3
M5	220	300
G1/8	680	1100
G1/4	1200	2100
G3/8	2300	4800
G1/2	3400	6100
G3/4	3200	8750
G1	2300	10.750

Valvola di blocco

Miniregolatore di pressione

■ HC34



	M	F
HC3418M5	G1/8	M5
HC341418	G1/4	G 1/8
HC343818	G3/8	G 1/8
HC341218	G1/2	G 1/8

HB40 anello singolo



■ HC35



	attacco	Portata (NI/min)
HC350018	G1/8	580
HC350014	G1/4	750

HB40 anello singolo



CARATTERISTICHE

Temperatura

-10° ÷ 90 °C

Fluido

0 ÷ 60 °C (tecnopolimero HC11-12)

Pressione Max

aria compressa, vuoto

Pressione di lavoro


15 bar

-0,99 ÷ 10 bar

Valvole manuali di linea

■ HC05


Valvola a corsoio



	attacco
HC0500M5	M5
HC050018	G1/8
HC050014	G1/4
HC050038	G3/8
HC050012	G1/2
HC050034	G3/4

■ HC07


Rubinetto a sfera F/F



	attacco
HC070018	G1/8
HC070014	G1/4
HC070038	G3/8
HC070012	G1/2
HC070034	G3/4

■ HC08


Rubinetto a sfera M/F



	attacco
HC080018	G1/8
HC080014	G1/4
HC080038	G3/8
HC080012	G1/2
HC080034	G3/4

■ HC09


Mini rubinetto a sfera F-F con maniglia nera



	attacco
HC090018	G1/8
HC090014	G1/4

■ HC10


Mini rubinetto a sfera M-F con maniglia nera



	attacco
HC100018	G1/8
HC100014	G1/4

■ HC11


Mini-valvola manuale 2/2



	Ø
HC110606	6
HC110808	8
HC111010	10
HC111212	12

■ HC12

Mini-valvola manuale 3/2



	Ø
HC120606	6
HC120808	8
HC121010	10
HC121212	12