


Straight union: KQ2H



Tube O.D. (mm)	Part No.	øD ⁽¹⁾	L	M	Effective area (mm ²) ⁽²⁾		Weight (g)
					Nylon	Urethane	
3.2	KQ2H23-00	9.6	31.5	15.5	3.4	2.9	3
4	KQ2H04-00	10.4	32.5	16	5.6	4	3
6	KQ2H06-00	12.8	34.5	17	13.1	10.4	4
8	KQ2H08-00	15.2	38.5	18.5	26.1	18.0	6
10	KQ2H10-00	18.5	42.5	21	41.5	29.5	11
12	KQ2H12-00	20.9	44.5	22	58.3	46.1	14
16	KQ2H16-00	26.5	51	25	113	(96)	24




Note1) øD: max. diameter
Note2) (): Values for soft nylon.

Different diameter straight: KQ2H



Tube O.D. (mm)		Part No.	øD ⁽¹⁾	L	M1	M2	Effective area (mm ²) ⁽²⁾		Weight (g)
a	b						Nylon	Urethane	
3.2	4	KQ2H23-04	10.4	32.5	15.5	16	3.4	2.9	3
4	6	KQ2H04-06	12.8	34.5	16	17	5.6	5.6	5
6	8	KQ2H06-08	15.2	38.5	17	18.5	13.1	10.4	6
8	10	KQ2H08-10	18.5	42	18.5	21	26.1	18.0	11
10	12	KQ2H10-12	20.9	44.5	21	22	41.5	29.5	14
12	16	KQ2H12-16	26.5	56.5	22	25	58.3	46.1	47



Note1) øD: max. diameter

Male elbow: KQ2L

<M5>



<M6>




<R(PT)>




Tube O.D. (mm)	Thread R(PT)	Part No.	H (Hex.)	øD1 ⁽¹⁾	øD2	L1	L2	A	M	Effective area (mm ²) ⁽²⁾		Weight (g)
										Nylon	Urethane	
3.2	M5	KQ2L23-M5	7	8.5	-	15.3	13.2	14.3	12.7	2.6	2.2	2.5
	1/8	KQ2L23-01S	10	9.6	10	17.5	21.5	22.5	15.5	3	2.5	8
	1/4	KQ2L23-02S	14				25.5	24.5				
4	M5	KQ2L04-M5	7	9.3	-	15.6	13.7	15.3	12.7	3.5	3.5	2.7
	M6	KQ2L04-M6	8				14.7	22				
	1/8	KQ2L04-01S	10	10.4	10	18	22	23	16	4.2	4.2	10
1/4	KQ2L04-02S	14	26				25	19				
6	M5	KQ2L06-M5	7	11.6	-	16.1	14.7	17.4	13.5	3.5	3.5	3.2
	M6	KQ2L06-M6	8				15.7	17.4				
	1/8	KQ2L06-01S	10	12.8	10	20	23	25.5	17	11.4	9.0	12
1/4	KQ2L06-02S	14	27				27.5	22				
8	3/8	KQ2L06-03S	17	15.2	12	23	29	29	18.5	21.6	14.9	33
	1/8	KQ2L08-01S	12				24.5	28				
	1/4	KQ2L08-02S	14	30.5	31.5	21	35					
10	3/8	KQ2L08-03S	17	18.5	17	26.5	27	32	21	35.2	25.0	36
	1/8	KQ2L10-01S	10				30	33				
	1/4	KQ2L10-02S	14	32	34.5	21	63					
12	1/2	KQ2L10-03S	17	20.9	17	28.5	36	37	22	50.2	39.7	65
	1/4	KQ2L12-02S	14				31	35.5				
	3/8	KQ2L12-03S	17	33	37	22	65					
16	1/2	KQ2L12-04S	22	26.5	20.9	34	37	39.5	25	71	(71)	101
	3/8	KQ2L16-03S	17				38	44.5				
	1/2	KQ2L16-04S	22	41	46	25	100	(84)	105			

<M5, M6>



<R(PT)>



*Reference dimensions after R(PT) thread installation.
Note1) øD1: max. diameter
Note2) (): Values for soft nylon.

